



EXPLANATIONS
ALL MEASURES ARE IN MILLIMETERS.

NOTES
THE SLIDING WINDOW SHALL BE TYPE AV70, SVALSON AB SWEDEN (+46 911 66725).

CONSTRUCTION
MOTOR, TRANSMISSION AND AUTOMATIC LOCKING SHALL BE PLACED WITHIN THE FRAME.

LOCKING
THE SLIDING WINDOW SHALL BE LOCKED AUTOMATICALLY IN CLOSED POSITION. (LOCKING IN 50 mm INTERVAL IS OPTIONAL.)

FINISH
THE ALUMINIUM PROFILES SHALL BE SATIN ANODISED. (OR ANY OTHER FINISH, FOR INSTANCE COLOUR COATED OR ANODISED IN OTHER COLOURS.)

GLASS
6 mm FLOAT GLASS. (OR OTHER TYPE OF GLASS WITH A THICKNESS BETWEEN 6 mm UP TO 20 mm FOR INSTANCE 8,76 mm P2A, 14 mm P6B OR DOUBLE GLAZING 4-12-4.)

OPENINGSPEED
THE OPENINGSPEED OF THE SLIDING WINDOW IS APPROX. 200 mm/SECOND.

REV	TYPE OF REVISION	DATE	SIGN



SVALSON AB
Phone +46 911-66725
Telefax +46 911-66680
http://www.svalson.com

Box 584
S-943 28 Öjebyn
SWEDEN

SLIDING WINDOW TYPE AV70		VIEW FROM OUTSIDE	<input checked="" type="checkbox"/>
DRAWN/DESIGN --	SCALE 1:10, 1:1	VIEW FROM INSIDE	<input type="checkbox"/>
DATE DD.MM.YY	DRAWING NUMBER AV70.	REV	