

6018

CE



2014.13 (eng)

Horizontally sliding window for indoor or outdoor installations


Robust, horizontally sliding, electrically operated window for both indoor and outdoor installation. The sliding window has an aluminium frame and can be equipped with insulating glass or up to 20 mm thick safety glass. In its standard version, the sliding window is satin anodized and equipped with D4-12 double glazing. The frame can be finished by powder coating, anodizing in other colours or stainless steel cladding. The sliding window is automatically locked in closed position and at intervals across the entire opening width. Operated by control switch with hold to run buttons.



EXAMPLES OF VERSIONS



OX (O=Fixed glass, X=Sliding glass)



XO



OLXO



XOOX



XOX



OXRO



OXXO



O



XO with overhead light

TECHNICAL INFORMATION

NAME	6018
DESCRIPTION	Robust, horizontally sliding, electrically operated window for indoor and outdoor installation.
WIDTH	Customers choice.
HEIGHT	Customers choice.
FRAME THICKNESS	60 mm
WIDTH SIDE POSTS	50 mm (53 mm on windows with overhead light).
HEIGHT TOP PROFILE	45 mm (50 mm on windows with overhead light).
HEIGHT OF BOTTOM PROFILE	5 mm plus a 6 mm guide.
GLASS FRAMES	30 mm
CONSTRUCTION	Motor, transmission and automatic locking are integrated within the frame.
LOCKING	Mechanical lock which automatically locks the window in closed position and at 50 mm intervals across the entire opening width. Options: key lock.
POWER SUPPLY	230 V AC transformer. Options: battery backup.
CONTROL SYSTEM	Electromechanical control system with hold to run buttons. Options: S3 control system (with soft start/stop, adjustable speed, optional push-and-release buttons, optional alarm closing, etc) and various control switches.
OPENING SPEED	Approx. 200 mm/sec.
GLASS	D4-12 double glazing is standard. Other glass up to 20 mm thick is available as an option, such as 14 mm, impact-resistant laminated glass, class P6B.
SURFACE COATING	Satin anodized aluminium is standard. Other surface coatings available as an option are powder coating, anodizing in various colours and stainless steel cladding.
MANUFACTURED BY	Svalson AB, Sweden

Visit www.svalson.com for more information.

Design and material subject to change without prior notice.

