

AH60

CE



2019.18 (eng)

Horizontally sliding window for indoor or outdoor installations


Robust, horizontally sliding, electrically operated window for both indoor and outdoor installation. The sliding window has an aluminium frame and can be equipped with insulating glass or up to 20 mm thick safety glass. In its standard version, the sliding window is satin anodized and equipped with D4-12 double glazing. The frame can be finished by powder coating, anodizing in other colours or stainless steel cladding. The sliding window is automatically locked in closed position and at intervals across the entire opening width. Operated by control switch with hold to run buttons.



EXAMPLES OF VERSIONS



OX (O=Fixed glass, X=Sliding glass)



XO



OLXO



XOOX



XOX



OXRO



OXXO



O



XO with overhead light

TECHNICAL INFORMATION

| | |
|--------------------------|---|
| NAME | AH60 |
| DESCRIPTION | Robust, horizontally sliding, electrically operated window for indoor and outdoor installation. |
| WIDTH | Customers choice. |
| HEIGHT | Customers choice. |
| FRAME THICKNESS | 60 mm |
| WIDTH SIDE POSTS | 50 mm (53 mm on windows with overhead light). |
| HEIGHT TOP PROFILE | 45 mm (50 mm on windows with overhead light). |
| HEIGHT OF BOTTOM PROFILE | 5 mm plus a 6 mm guide. |
| GLASS FRAMES | 30 mm |
| CONSTRUCTION | Motor, transmission and automatic locking are integrated within the frame. |
| LOCKING | Mechanical lock which automatically locks the window in closed position and at 50 mm intervals across the entire opening width. Options: key lock. |
| POWER SUPPLY | 230 V AC transformer. Options: battery backup. |
| CONTROL SYSTEM | Electromechanical control system with hold to run buttons. Options: S3 control system (with soft start/stop, adjustable speed, optional push-and-release buttons, optional alarm closing, etc) and various control switches. |
| OPENING SPEED | Approx. 200 mm/sec. |
| GLASS | D4-12 double glazing is standard. Other glass up to 20 mm thick is available as an option, such as 14 mm, impact-resistant laminated glass, class P6B. |
| SURFACE COATING | Satin anodized aluminium is standard. Other surface coatings available as an option are powder coating, anodizing in various colours and stainless steel cladding. |
| MANUFACTURED BY | Svalson AB, Sweden |

Visit www.svalson.com for more information.

Design and material subject to change without prior notice.

